


The revolutionary EasyCare is a fully configurable healthcare bed offered at price points ideal for care facilities of any size. Enhanced functionality and mobility features allow the bed to be configured to meet a variety of needs – for both the patient and caregiver. Create the bed that works best for your patients and facility with features such as integrated width expansion, pedal locking system, reinforced sleep deck, redesigned panel retentions, and new mattress corner stops that adjust with the bed width.




Enhanced Features and New Options


- Intuitive two-pedal locking system is centrally positioned at the foot end of the bed and easily visible due to color-coded status indicators. Available as a standard option with the roll-at-any height configuration.
- Integrated width extension provides a sleep surface that expands and retracts from 35", 39" and 42" and quickly adjusts to move through doorways while compliant to HBSW entrapment guidelines. Available at time of order.
- A restructured and more robust sleep surface and panel mounting mechanism designed to provide added stability and extended product life.
- Corner mattress stops provide greater security of the mattress surface and easily adjust to the expanded widths of the frame up to 42 inches.
- AdvanceCare positioning now available as an option on EasyCare. Includes Gravity Assist, Comfort Chair, and Auto-Transfer Height functionality.




Pedal Lock



Integrated Width



Corner Mattress Stops



Panel Retention

Standard Features

- A. 7-inch to 30-inch travel range** offers safety, whether resting at an ultra low height or providing care at the highest height.
- B. Revolutionary arched legs** deliver a super-strong wide stance for equipment clearance.
- C. Four-section mattress support platform** offers a full range of comfort and therapeutic positions designed to reduce patient and caregiver injuries and potentially reduce shear.
- D. Therapeutic grid surface** offers improved airflow and ultimate support for the newly reinforced sleep surface.
- E. Hand pendant and optional staff control** allow both patient and caregiver the flexibility to adjust the bed into the desired position for comfort or care needs.
- F. Toroidal architecture** engineering of the bed's steel frame is up to 30 times stronger than competitor's angle iron bed frames.
- G. EasyLift Leg Lift** provides quick positioning of the knee section of the bed for improved circulation – ideal for patients with blood flow disorders.
- H. Four DC motors** supply amazingly quiet and smooth operation during frame articulation. *The EasyCare now features a 4-year warranty on the frame electronics.*

Ordering and configuring your bed for your specific needs is **Easy-ier** than ever too! We've made getting a customized EasyCare as easy as 1 - 2 - 3.

- 1** Select your mobility preference (roll-in-low for the absolute safest platform or roll-at-any-height to give a safe and versatile option)
- 2** Select your bed positioning option (traditional Standard or Joerns proprietary AdvancedCare positioning)
- 3** Select your bed options (fixed or integrated width, assist devices, optional surfaces designed to work in concert with EasyCare's articulation)

Technical Specifications

| Mobility Selections | Roll-in-Low | | Roll-at-any-Height | |
|--------------------------|---|--------------------|---|--------------------|
| Functionality Selections | Standard: 3 Function | AdvanceCare | Standard: 3 Function | AdvanceCare |
| Low Height | 7" | | 7" | |
| High Height | 30" | | 30" | |
| Bed Length | 76" | 80" | 76" | 80" |
| Length Ext Options | 4" Extender | | 4" Extender | |
| Bed Width | 35" | | 35" | |
| Width Ext. Options | Integrated Width Exp | CareWide Accessory | Integrated Width Exp | CareWide Accessory |
| Casters | Four casters (two locking) | | SafeLock Pedal Locking System | |
| Safe Work Load | 500 lb at 76" length 600 lb at 80" length | | 500 lb at 76" length 600 lb at 80" length | |
| Underbed Clearance | 23 ¾" | | 23 ¾" | |
| Product Weight | 220 lb | | 230 lb | |
| Max Back Angle | 65 Degrees to Horizontal | | 65 Degrees to Horizontal | |
| Max Knee Angle | 35 Degrees to Horizontal | | 35 Degrees to Horizontal | |
| MSP Translation | <1" | | <1" | |
| Mobility Height | 7" | | 7" - 30" | |
| Mains Voltage | 120 VAC | | 120 VAC | |
| Frequency | 60 Hz | | 60 Hz | |
| Input Current | 4.0 Amps | | 4.0 Amps | |
| Electrical Protection | Class I Hospital Grade | | Class I Hospital Grade | |
| Duty Cycle | 10%: 2 Min On/18 Min Off | | 10%: 2 Min On/18 Min Off | |
| Circuit Protection | Auto Reset Current Sensor | | Auto Reset Current Sensor | |