


## Tub-Mount Swivel Sliding Transfer Bench


77762

### Parts Reference



### Assembly Instructions

1. Take the leg frame with the handlebar (Part A), and lay it flat on the ground.
2. Determine which direction you want the seat to face in your bathtub. The leg frame with the handlebar (Part A) will be the side that goes inside the bathtub.
3. There are two sliding rails (Part C): one rail has 4 brass push buttons (front rail), and the other rail has 2 brass push buttons (rear rail).
4. If you prefer to sit facing left (if looking at the tub from outside), take the rail with 4 push buttons (front rail), and insert it into tube X (or insert it into tube Y if you want to sit facing right). The push buttons should be facing outwards. (NOTE: the smaller push buttons are for the sliding rail locking mechanisms). Make sure the larger button snaps firmly into the leg frame.
5. Insert the other sliding rail (rear) into the other side of the leg frame (Part A), making sure the button snaps firmly into place.



6. Take the seat with the attached sliding rings (Part D), and align the sliding rings with the rails, so that the locking side of the seat (the side with the red tabs) is on



the same rail as the 4 brass push buttons (front rail). Insert both sliding rails into the sliding rings under the seat. Push in the push buttons to slide the seat easily onto the rails.

7. Take the tub clamp (Part B), and insert the sliding rails into it. Make sure the brass buttons snap firmly into place.



8. Take the 2 legs (Part E), and insert them into the leg frames (Part A). Set the bench height by using the same button-hole location for each leg. Make sure the buttons snap firmly into place. For your safety, adjust the rubber tips on the legs by turning them outward for maximum floor contact.



9. Take the backrest (Part F), and press the two brass push buttons on the frame of the backrest. Insert the backrest into the tubes underneath the seat, and push it in until the brass push buttons snap firmly into place.



10. Set the bench into your bathtub, placing the leg frame with the handlebar inside the bathtub and the tub clamp on the bathtub side-wall. Attach the tub clamp to the bathtub side-wall and securely fasten the tub clamp to the side-wall using the turn-knob.
11. Make sure the sliding rails and seat are level by adjusting the legs (using the same button-hole location for each leg).



Thank you for purchasing an Eagle Health Supplies product!

Helpful instructional assembly videos available at [www.EagleHealth.com](http://www.EagleHealth.com).

**If any push button/pin does not completely snap into place while assembling, or if you feel the bench is not secure, please do not use the bench, and notify your Authorized Dealer immediately.**

To register your product for the Limited One-Year Warranty, please complete and return the included Warranty Card, or register online at [www.EagleHealth.com](http://www.EagleHealth.com).

## Tips for Care and Use

### Locking Mechanism

Lock the seat into place by making sure the slide ring snaps firmly onto the brass push button at the end of the sliding rail (shown below). Release the locking mechanism by pressing down on the red tab of the locked slide ring.

**UNLOCKED**



**LOCKED**



### Swivel Seat

Press down on the red tab located under the center of the seat's front edge to turn the swivel seat, and rotate the seat slightly. Once the seat starts to swivel, release the red tab. The swivel seat locks every 90 degrees.

### Cleaning

Rinse off the bench with warm water after each use to prevent dirt, soap scum, and mineral deposits from forming which could affect proper operation. We recommend regularly cleaning the seat and back with a soft cloth, warm water and mild soap, or with a soft cloth and any non-bleach cleaner.

### Maintenance

Built up soap scum, mineral deposits, or watermarks may cause the brass push buttons/pins to stick or may cause the seat to not slide smoothly along the rails. To help, spray lubricant, such as WD-40, on the brass push buttons/pins to loosen the buttons/pins, or along the sliding rails to maintain a smooth slide.

To maintain a smooth swivel, regularly use WD-40, or other lubricant, and spray in between the swivel plates, towards the middle swivel bolt.



**EAGLE HEALTH SUPPLIES INC.**  
[www.eaglehealth.com](http://www.eaglehealth.com)

# Instruction Pamphlet

**For Tub-Mount Swivel Sliding  
Transfer Bench**

**77761 / 77762**

**For Your Comfort. For Your Safety.**

**For Your Independence. For YOU.**